

Options

Accessories

Deck mount handshower fixing station

Aqualisa Products Limited, The Flyer's Way, Westerham, Kent TN16 1DE

Customer Helpline: 01959 560010 Facsimile: 01959 560030

Website: www.aqualisa.co.uk E-mail: enquiries@aqualisa.co.uk

Important information



This product must be installed by a competent person in accordance with the relevant current Water Supply Regulations.

The Aqualisa Options range of accessories are supplied complete with a 2 year guarantee.

In the event of any product problems, please contact the Aqualisa Customer Helpline on 01959 560010.

Components - deck mount handshower fixing station




Deck mount handshower fixing station

1

If fitted, remove the metal thrust washer and locking nut from the handshower fixing assembly.

2

Offer the assembly into position within the mounting surface ensuring the base O' ring is in place. A Ø35mm – 40mm hole is required.



3

Place the thrust washer and locking nut onto the assembly and secure to the underside of the mounting surface using a suitable tool.



4

Construct a suitable connection from the blended outlet pipe to the flexible hose (supplied separately) and offer up through the underside of the mounting surface through the fixing station.



5

Ensuring the hose washer is in place connect the flexible hose to the fixing station mounting connector.




6

If required, fit the angled connector into the fixing station mounting connector ensuring the hose washer is fitted.



7

Ensuring the hose washer is in place fit the handset (supplied separately) to the relevant mounting connector and place within the fixing station.



Options

Accessories

Wall mount handshower fixing station

Components – Wall mounted handshower fixing station



Wall station

1

Place wall station in the required location on the finished wall surface and mark and prepare the fixing points, using the fixings provided, if suitable.



2

Secure the wall mount fixing station to the wall using the fixings provided, if suitable.

