
## **ELIS∧**™ Aquahub™

### COMPATIBLE WITH:


DC001CH / DC001BB / DC001MB DC002CH / DC002BB / DC002MB DC003CH / DC003BB / DC003MB PB002CH / PB002BB / PB002MB PB003CH / PB003BB / PB003MB

### AQUAHUB UNIVERSAL CONCEDED INSTALLATION BOX - AHUB1


DIMENSIONAL DRAWINGS



FRONT



SIDE



The company reserves the right to alter, change or modify the product or product specifications without prior warning. Please refer to the installation guides for technical information.

# ELIS∧ Aquahub™

### COMPATIBLE WITH:

DC001CH / DC001BB / DC001MB DC002CH / DC002BB / DC002MB DC003CH / DC003BB / DC003MB PB002CH / PB002BB / PB002MB PB003CH / PB003BB / PB003MB

#### AQUAHUB CONCEALED UNIVERSAL MIXER

TECHNICAL SPECIFICATIONS

Min Pressure	1 bar
Max Pressure	10 bar
Fitting connections	3/4 "
Outlet connections	3/4"
Inlet supply positions	Left hot, Right cold
Features	Front and rear mounting options
	2 stage fixing for 1st and 2nd fix installations
	Slim 60mm minimum installation depth
	Reversible inlets in case plumbed incorrectly
	One box suitable for 1,2 and 3 outlets as well as push button or dial operation
	Intergrated isolation valves
	8 fixing points for flexible installation
	Theromstatically controlled
	Flow control
	Quality brass valve
	Flush block testing plate
Guarantee period	15 years (Please see guarantee Ts and Cs for more information)